

18 KG



- Machinery for professional use
- Structure made entirely of AISI 304 stainless steel
- Domestic production of an asynchronous ventilated motor
- Abrasive walls that can be easily replaced without the use of tools
- Electronic solenoid valve for water inlet
- Micro cover and door
- Shatter-proof transparent plastic cover
- Stainless steel cover (on request)
- Standard exhaust filter drawer
- Visible and practical digital controls
- External electrical device protected by insulated plastic box
- Multi-function digital timer
- Manual button for product unloading
- Floor or wall exhaust manifold
- Belt drive
- CE standards
- Manufactured in Italy

TECHNICAL SPECIFICATIONS	
Power supply (Volt / Hz)	230/50 - 230 · 400/50
Power (Kwatt / Hp)	0.90 (1.20)
Peeler plate turns	320
Potato production per hour	500
Maximum load of potatoes	18
Cleaning cycle time	120-150
Water temperature	5-20
Flexible hose supply	3/4
Side discharge manifold	ø50
Lower exhaust manifold	ø40
Single / three phase net weight (Kg)	43.5 / 43.5
Gross weight mono / tri phase (Kg)	51.0 / 51.0
Dimensions (mm)	B. 530 D. 660 H. 950
Packing size (mm)	B. 670 D. 590 H. 1120